

Comparison of Trade / Industrial Towers

Description	Trade King Tower	Industrial Tower
Quality	Trade	Industrial
Usage	Regular use	Daily use
Working heights	2.84m – 9.6m	3.2m – 14.2m
Tower width*	0.73m (2'5")	0.85m (2'10") / 1.45m (4'9")
Tower length*	1.55m (5'1")	1.8m (5'11") / 2.5m (8'2")
Platform width	0.6m (2')	0.6m (2')
Platform height adjustment	0.25m (10") increments	0.5m (1'8") increments
Safe working load per platform	230kg (36.2 stone)	275kg (43.3 stone)
Safe working load per tower	860kg (135.4 stone)	950kg (149.6 stone)
Height adjustable wheels	Optional upgrade	Yes
Braces	25mm x 57mm rectangular section	51mm round tube
Toeboard	Wooden - 4 piece	Single piece folding aluminium
Base section	Foldable / Non-foldable	Non-foldable
Frame uprights	51mm round tube	51mm round tube
Ladder rungs	40mm round tube	51mm round tube
Optional extras	Height adjustable wheels Height adjustable baseplates Large Telescopic Outriggers Scaffold Tags Stair Tower option	Height adjustable baseplates Large Telescopic Outriggers Scaffold Tags
Product weight	7.1m Non-foldable - 115.2kg	7.2m 850 1.8m - 145.7kg

*Measured centre-to-centre on frame uprights